

globus gass copy Reference Manual

8.6

Generated by Doxygen 1.4.7

Wed Jul 25 08:06:51 2012

Contents

1	globus gass copy Main Page	1
2	globus gass copy Data Structure Index	1
3	globus gass copy File Index	1
4	globus gass copy Data Structure Documentation	2
5	globus gass copy File Documentation	6

1 globus gass copy Main Page

The Globus GASS Copy library is motivated by the desire to provide a uniform interface to transfer files specified by different protocols. The goals in doing this are to:

- Provide a robust way to describe and apply file transfer properties for a variety of protocols. These include the standard HTTP, FTP and GSIFTP options. Some of the new file transfer capabilities in GSIFTP are parallel, striping, authentication and TCP buffer sizing.
- Provide a service to support nonblocking file transfer and handle asynchronous file and network events.
- Provide a simple and portable way to implement file transfers.

Any program that uses Globus GASS Copy functions must include "globus_gass_copy.h".

2 globus gass copy Data Structure Index

2.1 globus gass copy Data Structures

Here are the data structures with brief descriptions:

globus_gass_copy_glob_stat_t (Glob expanded entry information)	2
globus_gass_copy_state_s (The state structure contains all that is required to perform a file transfer from a source to a destination)	3
globus_i_gass_copy_buffer_t (The buffer structure used for read/write queue entries)	3
globus_i_gass_copy_cancel_s (Gass copy cancel struct)	4
globus_i_gass_copy_monitor_t (The state monitor struct)	4
globus_i_gass_copy_state_target_s (GASS copy target (e.g)	4

3 globus gass copy File Index

3.1 globus gass copy File List

Here is a list of all documented files with brief descriptions:

globus_gass_copy.c (Globus GASS Copy library)	6
globus_gass_copy.h (Header file for the gass copy library)	18

4 globus gass copy Data Structure Documentation

4.1 globus_gass_copy_glob_stat_t Struct Reference

Glob expanded entry information.

Data Fields

- **globus_gass_copy_glob_entry_t** type
- **char * unique_id**
- **char * symlink_target**
- **int mode**
- **int mdtm**
- **globus_off_t** size

4.1.1 Detailed Description

Glob expanded entry information.

4.1.2 Field Documentation

4.1.2.1 globus_gass_copy_glob_entry_t globus_gass_copy_glob_stat_t::type

The file type of the entry.

4.1.2.2 char* globus_gass_copy_glob_stat_t::unique_id

A string that uniquely identifies the data that the entry refers to.

A file and a symlink to that file will have the same unique_id. It is NULL for when not available.

4.1.2.3 char* globus_gass_copy_glob_stat_t::symlink_target

This points to the full path of the target of a symlink.

It is NULL for non-symlinks or when not available.

4.1.2.4 int globus_gass_copy_glob_stat_t::mode

An integer specifying the mode of the file.

It is set to -1 when not available.

4.1.2.5 int globus_gass_copy_glob_stat_t::mdtm

An integer specifying the modification time of the file.

It is set to -1 when not available.

4.1.2.6 globus_off_t globus_gass_copy_glob_stat_t::size

A globus_off_t specifying the size of the file.

It is set to -1 when not available.

4.2 globus_gass_copy_state_s Struct Reference

The state structure contains all that is required to perform a file transfer from a source to a destination.

Data Fields

- globus_i_gass_copy_target_t source
- globus_i_gass_copy_target_t dest
- globus_i_gass_copy_monitor_t monitor
- globus_mutex_t mutex
- globus_i_gass_copy_cancel_status_t cancel

4.2.1 Detailed Description

The state structure contains all that is required to perform a file transfer from a source to a destination.

4.2.2 Field Documentation

4.2.2.1 globus_i_gass_copy_target_t globus_gass_copy_state_s::source

Source information for the file transfer.

4.2.2.2 globus_i_gass_copy_target_t globus_gass_copy_state_s::dest

Dest information for the file transfer.

4.2.2.3 globus_i_gass_copy_monitor_t globus_gass_copy_state_s::monitor

Used for signalling from the various callback functions.

4.2.2.4 globus_mutex_t globus_gass_copy_state_s::mutex

coordinates the modifying of the state, aside from the target structures

4.2.2.5 globus_i_gass_copy_cancel_status_t globus_gass_copy_state_s::cancel

indicates the status of the cancel operation.

4.3 globus_i_gass_copy_buffer_t Struct Reference

The buffer structure used for read/write queue entries.

4.3.1 Detailed Description

The buffer structure used for read/write queue entries.

4.4 globus_i_gass_copy_cancel_s Struct Reference

gass copy cancel struct

4.4.1 Detailed Description

gass copy cancel struct

4.5 globus_i_gass_copy_monitor_t Struct Reference

The state monitor struct.

4.5.1 Detailed Description

The state monitor struct.

4.6 globus_i_gass_copy_state_target_s Struct Reference

GASS copy target (e.g.

Data Fields

- `char * url`
- `globus_gass_copy_attr_t * attr`
- `globus_mutex_t mutex`
- `globus_fifo_t queue`
- `int n_pending`
- `int n_simultaneous`
- `int n_complete`
- `globus_i_gass_copy_target_status_t status`
- `globus_gass_copy_url_mode_t mode`
- `union {
 struct {
 } ftp
 struct {
 globus_gass_transfer_request_t request
 } gass
 struct {
 globus_bool_t free_handle
 globus_bool_t seekable
 } io
} data`

4.6.1 Detailed Description

GASS copy target (e.g.

source, destination) transfer information.

4.6.2 Field Documentation

4.6.2.1 `char* globus_i_gass_copy_state_target_s::url`

url for file transfer

4.6.2.2 `globus_gass_copy_attr_t* globus_i_gass_copy_state_target_s::attr`

attributes to control file transfer

4.6.2.3 `globus_mutex_t globus_i_gass_copy_state_target_s::mutex`

coordinates the modifying of the target structure

4.6.2.4 `globus_fifo_t globus_i_gass_copy_state_target_s::queue`

a queue to manage the reading/writing of data buffers

4.6.2.5 `int globus_i_gass_copy_state_target_s::n_pending`

Used for keeping track of reads/writes in the read/write queue.

4.6.2.6 `int globus_i_gass_copy_state_target_s::n_simultaneous`

Used to limit the number of `n_pending`.

4.6.2.7 `int globus_i_gass_copy_state_target_s::n_complete`

Used to compute the offset for ftp writes.

4.6.2.8 `globus_i_gass_copy_target_status_t globus_i_gass_copy_state_target_s::status`

signifies the target has been successfully setup

4.6.2.9 `globus_gass_copy_url_mode_t globus_i_gass_copy_state_target_s::mode`

mode used to identify the below target union struct.

4.6.2.10 `struct { ... } globus_i_gass_copy_state_target_s::ftp`

ftp specific data

4.6.2.11 `globus_gass_transfer_request_t globus_i_gass_copy_state_target_s::request`

GASS equivalent of a handle.

4.6.2.12 `struct { ... } globus_i_gass_copy_state_target_s::gass`

GASS specific data.

4.6.2.13 `globus_bool_t globus_i_gass_copy_state_target_s::free_handle`

If the IO handle was passed as an argument then FALSE If the IO handle was created internally then TRUE.

4.6.2.14 globus_bool_t globus_i_gass_copy_state_target_s::seekable

Can globus_io_file_seek() be performed on this handle?

4.6.2.15 struct { ... } globus_i_gass_copy_state_target_s::io

IO specific data.

4.6.2.16 union { ... } globus_i_gass_copy_state_target_s::data

data required to perform each type of transfer

5 globus gass copy File Documentation

5.1 globus_gass_copy.c File Reference

Globus GASS Copy library.

Functions

- globus_result_t globus_gass_copy_handle_init (globus_gass_copy_handle_t *handle, globus_gass_copy_handleattr_t *attr)
- globus_result_t globus_gass_copy_handle_destroy (globus_gass_copy_handle_t *handle)
- globus_result_t globus_gass_copy_set_buffer_length (globus_gass_copy_handle_t *handle, int length)
- globus_result_t globus_gass_copy_get_buffer_length (globus_gass_copy_handle_t *handle, int *length)
- globus_result_t globus_gass_copy_set_no_third_party_transfers (globus_gass_copy_handle_t *handle, globus_bool_t no_third_party_transfers)
- globus_result_t globus_gass_copy_get_no_third_party_transfers (globus_gass_copy_handle_t *handle, globus_bool_t *no_third_party_transfers)
- globus_result_t globus_gass_copy_set_allocate (globus_gass_copy_handle_t *handle, globus_bool_t send_allo)
- globus_result_t globus_gass_copy_set_stat_on_expand (globus_gass_copy_handle_t *handle, globus_bool_t always_stat)
- globus_result_t globus_gass_copy_set_partial_offsets (globus_gass_copy_handle_t *handle, globus_off_t offset, globus_off_t end_offset)
- globus_result_t globus_gass_copy_get_partial_offsets (globus_gass_copy_handle_t *handle, globus_off_t *offset, globus_off_t *end_offset)
- globus_result_t globus_gass_copy_attr_init (globus_gass_copy_attr_t *attr)
- globus_result_t globus_gass_copy_attr_set_ftp (globus_gass_copy_attr_t *attr, globus_ftp_client_operationattr_t *ftp_attr)
- globus_result_t globus_gass_copy_attr_set_io (globus_gass_copy_attr_t *attr, globus_io_attr_t *io_attr)
- globus_result_t globus_gass_copy_attr_set_gass (globus_gass_copy_attr_t *attr, globus_gass_transfer_requestattr_t *gass_attr)
- globus_result_t globus_gass_copy_get_url_mode (char *url, globus_gass_copy_url_mode_t *mode)
- globus_result_t globus_gass_copy_register_performance_cb (globus_gass_copy_handle_t *handle, globus_gass_copy_performance_cb_t callback, void *user_arg)
- globus_result_t globus_gass_copy_get_status (globus_gass_copy_handle_t *handle, globus_gass_copy_status_t *status)
- const char * globus_gass_copy_get_status_string (globus_gass_copy_handle_t *handle)

- `globus_result_t globus_gass_copy_url_to_url (globus_gass_copy_handle_t *handle, char *source_url, globus_gass_copy_attr_t *source_attr, char *dest_url, globus_gass_copy_attr_t *dest_attr)`
- `globus_result_t globus_gass_copy_url_to_handle (globus_gass_copy_handle_t *handle, char *source_url, globus_gass_copy_attr_t *source_attr, globus_io_handle_t *dest_handle)`
- `globus_result_t globus_gass_copy_handle_to_url (globus_gass_copy_handle_t *handle, globus_io_handle_t *source_handle, char *dest_url, globus_gass_copy_attr_t *dest_attr)`
- `globus_result_t globus_gass_copy_register_url_to_url (globus_gass_copy_handle_t *handle, char *source_url, globus_gass_copy_attr_t *source_attr, char *dest_url, globus_gass_copy_attr_t *dest_attr, globus_gass_copy_callback_t callback_func, void *callback_arg)`
- `globus_result_t globus_gass_copy_register_url_to_handle (globus_gass_copy_handle_t *handle, char *source_url, globus_gass_copy_attr_t *source_attr, globus_io_handle_t *dest_handle, globus_gass_copy_callback_t callback_func, void *callback_arg)`
- `globus_result_t globus_gass_copy_register_handle_to_url (globus_gass_copy_handle_t *handle, globus_io_handle_t *source_handle, char *dest_url, globus_gass_copy_attr_t *dest_attr, globus_gass_copy_callback_t callback_func, void *callback_arg)`
- `globus_result_t globus_gass_copy_cache_url_state (globus_gass_copy_handle_t *handle, char *url)`
- `globus_result_t globus_gass_copy_flush_url_state (globus_gass_copy_handle_t *handle, char *url)`
- `globus_result_t globus_gass_copy_set_user_pointer (globus_gass_copy_handle_t *handle, void *user_pointer)`
- `globus_result_t globus_gass_copy_get_user_pointer (globus_gass_copy_handle_t *handle, void **user_data)`
- `globus_result_t globus_gass_copy_cancel (globus_gass_copy_handle_t *handle, globus_gass_copy_callback_t cancel_callback, void *cancel_callback_arg)`
- `globus_result_t globus_l_gass_copy_target_cancel (globus_i_gass_copy_cancel_t *cancel_info)`

5.1.1 Detailed Description

Globus GASS Copy library.

See also:

See the detailed description in `globus_gass_copy.h` (p. 18)

5.1.2 Function Documentation

5.1.2.1 `globus_result_t globus_gass_copy_handle_init (globus_gass_copy_handle_t * handle, globus_gass_copy_handleattr_t * attr)`

Initialize a GASS Copy handle.

A `globus_gass_copy_handle` must be initialized before any transfers may be associated with it. This function initializes a `globus_gass_copy_handle` to be used for doing transfers, this includes initializing a `globus_ftp_client_handle` which will be used for doing any ftp/gsiftp transfers. The same handle may be used to perform multiple, consecutive transfers. However, there can only be one transfer associated with a particular handle at any given time. After all transfers to be associated with this handle have completed, the handle should be destroyed by calling `globus_gass_copy_handle_destroy()` (p. 8).

Parameters:

handle The handle to be initialized

attr The handle attributes used to use with this handle

Returns:

This function returns `GLOBUS_SUCCESS` if successful, or a `globus_result_t` indicating the error that occurred.

See also:

globus_gass_copy_handle_destroy() (p. 8) , **globus_gass_copy_handleattr_init()**, **globus_ftp_client_handle_init()**

5.1.2.2 globus_result_t globus_gass_copy_handle_destroy (globus_gass_copy_handle_t * *handle*)

Destroy a GASS Copy handle.

Destroy a **gass_copy_handle**, which was initialized using **globus_gass_copy_handle_init()** (p. 7), that will no longer be used for doing transfers. Once the handle is destroyed, no further transfers should be associated with it.

Parameters:

handle The handle to be destroyed

Returns:

This function returns GLOBUS_SUCCESS if successful, or a **globus_result_t** indicating the error that occurred.

See also:

globus_gass_copy_handle_init() (p. 7), **globus_ftp_client_handle_destroy()**

5.1.2.3 globus_result_t globus_gass_copy_set_buffer_length (globus_gass_copy_handle_t * *handle*, int *length*)

Set the size of the buffer to be used for doing transfers.

This function allows the user to set the size of the buffer that will be used for doing transfers, if this function is not called the buffer size will default to 1M.

Parameters:

handle Set the buffer length for transfers associated with this handle.

length The length, in bytes, to make the buffer.

Returns:

This function returns GLOBUS_SUCCESS if successful, or a **globus_result_t** indicating the error that occurred.

5.1.2.4 globus_result_t globus_gass_copy_get_buffer_length (globus_gass_copy_handle_t * *handle*, int * *length*)

Get the size of the buffer being used for doing transfers.

This function allows the user to get the size of the buffer that is being used for doing transfers.

Parameters:

handle Get the buffer length for transfers associated with this handle.

length The length, in bytes, of the buffer.

Returns:

This function returns GLOBUS_SUCCESS if successful, or a **globus_result_t** indicating the error that occurred.

5.1.2.5 globus_result_t globus_gass_copy_set_no_third_party_transfers (globus_gass_copy_handle_t * handle, globus_bool_t no_third_party_transfers)

Turn third-party transfers on or off.

(They are on by default.)

This function allows the user to turn third-party transfers on or off for ftp to ftp transfers associated with a particular handle. This is often desired if one of the servers involved in the transfer does not allow third-party transfers.

Parameters:

handle Turn third-party transfers on or off for transfers associated with this handle. They are on by default.

no_third_party_transfers GLOBUS_FALSE if third-party transfers should be used. GLOBUS_TRUE if third-party transfers should not be used.

Returns:

This function returns GLOBUS_SUCCESS if successful, or a globus_result_t indicating the error that occurred.

5.1.2.6 globus_result_t globus_gass_copy_get_no_third_party_transfers (globus_gass_copy_handle_t * handle, globus_bool_t * no_third_party_transfers)

See if third-party transfers are turned on or off.

(They are on by default.)

This function allows the user to see if third-party transfers are turned on or off for ftp to ftp transfers associated with a particular handle. This is often desired if one of the servers involved in the transfer does not allow third-party transfers.

Parameters:

handle See if third-party transfers are turned on or off for transfers associated with this handle. They are on by default.

no_third_party_transfers GLOBUS_FALSE if third-party transfers should be used. GLOBUS_TRUE if third-party transfers should not be used.

Returns:

This function returns GLOBUS_SUCCESS if successful, or a globus_result_t indicating the error that occurred.

5.1.2.7 globus_result_t globus_gass_copy_set_allocate (globus_gass_copy_handle_t * handle, globus_bool_t send_allo)

Set allo on or off.

5.1.2.8 globus_result_t globus_gass_copy_set_stat_on_expand (globus_gass_copy_handle_t * handle, globus_bool_t always_stat)

Make globus_gass_copy_expand_url() always send stat info.

5.1.2.9 **globus_result_t globus_gass_copy_set_partial_offsets** (**globus_gass_copy_handle_t** * *handle*, **globus_off_t** *offset*, **globus_off_t** *end_offset*)

Set the offsets to be used for doing partial transfers.

This function allows the user to set the offsets that will be used for doing partial transfers. An offset of -1 will disable partial transfers. An end_offset of -1 means EOF.

Parameters:

handle Set the offsets for partial transfers associated with this handle.

offset The starting offset for the partial transfer.

end_offset The ending offset for the partial transfer.

Returns:

This function returns GLOBUS_SUCCESS if successful, or a globus_result_t indicating the error that occurred.

5.1.2.10 **globus_result_t globus_gass_copy_get_partial_offsets** (**globus_gass_copy_handle_t** * *handle*, **globus_off_t** * *offset*, **globus_off_t** * *end_offset*)

Get the offsets being used for doing partial transfers.

This function allows the user to get the offsets that are being used for doing partial transfers. An offset of -1 means partial transfers are disabled.

Parameters:

handle Get the offsets for partial transfers associated with this handle.

offset The starting offset for the partial transfer.

end_offset The ending offset for the partial transfer.

Returns:

This function returns GLOBUS_SUCCESS if successful, or a globus_result_t indicating the error that occurred.

5.1.2.11 **globus_result_t globus_gass_copy_attr_init** (**globus_gass_copy_attr_t** * *attr*)

Initialize an attribute structure.

The globus_gass_copy_attr_t can be used to pass the globus_gass_copy library information about how a transfer should be performed. It must first be initialized by calling this function. Then any or all of the following functions may be called to set attributes associated with a particular protocol: **globus_gass_copy_attr_set_ftp()** (p. 11), **globus_gass_copy_attr_set_gass()** (p. 11), **globus_gass_copy_attr_set_io()** (p. 11). Any function which takes a globus_gass_copy_attr_t as an argument will also accept GLOBUS_NULL, in which case the appropriate set of default attributes will be used.

Parameters:

attr The attribute structure to be initialized

Returns:

This function returns GLOBUS_SUCCESS if successful, or a globus_result_t indicating the error that occurred.

See also:

globus_gass_copy_attr_set_ftp() (p. 11), **globus_gass_copy_attr_set_gass()** (p. 11), **globus_gass_copy_attr_set_io()** (p. 11), **globus_gass_copy_get_url_mode()** (p. 12).

5.1.2.12 globus_result_t globus_gass_copy_attr_set_ftp (globus_gass_copy_attr_t * attr, globus_ftp_client_operationattr_t * ftp_attr)

Set the attributes for ftp/gsiftp transfers.

In order to specify attributes for ftp/gsiftp transfers, a **globus_ftp_client_operationattr_t** should be initialized and its values set using the appropriate **globus_ftp_client_operationattr_*** functions. The **globus_ftp_client_operationattr_t *** can then be passed to the **globus_gass_copy_attr_t** via this function.

Parameters:

attr A **globus_gass_copy** attribute structure

ftp_attr The ftp/gsiftp attributes to be used

Returns:

This function returns **GLOBUS_SUCCESS** if successful, or a **globus_result_t** indicating the error that occurred.

See also:

globus_gass_copy_attr_init() (p. 10), **globus_gass_copy_attr_set_gass()** (p. 11), **globus_gass_copy_attr_set_io()** (p. 11), **globus_gass_copy_get_url_mode()** (p. 12), **globus_ftp_client_operationattr_***

5.1.2.13 globus_result_t globus_gass_copy_attr_set_io (globus_gass_copy_attr_t * attr, globus_io_attr_t * io_attr)

Set the attributes for file transfers.

In order to specify attributes for file transfers, a **globus_io_attr_t** should be initialized and its values set using the appropriate **globus_io_attr_*** functions. The **globus_io_attr_t** can then be passed to the **globus_gass_copy_attr_t** via this function.

Parameters:

attr A **globus_gass_copy** attribute structure

io_attr The file attributes to be used

Returns:

This function returns **GLOBUS_SUCCESS** if successful, or a **globus_result_t** indicating the error that occurred.

See also:

globus_gass_copy_attr_init() (p. 10), **globus_gass_copy_attr_set_gass()** (p. 11), **globus_gass_copy_attr_set_ftp()** (p. 11), **globus_gass_copy_get_url_mode()** (p. 12), **globus_io_attr_***

5.1.2.14 globus_result_t globus_gass_copy_attr_set_gass (globus_gass_copy_attr_t * attr, globus_gass_transfer_requestattr_t * gass_attr)

Set the attributes for http/https transfers.

In order to specify attributes for http/https transfers, a `globus_gass_transfer_requestattr_t` should be initialized and its values set using the appropriate `globus_gass_transfer_requestattr_*` functions. The `globus_gass_transfer_requestattr_t` can then be passed to the `globus_gass_copy_attr_t` via this function.

Parameters:

attr A `globus_gass_copy` attribute structure
gass_attr The http/https attributes to be used

Returns:

This function returns `GLOBUS_SUCCESS` if successful, or a `globus_result_t` indicating the error that occurred.

See also:

`globus_gass_copy_attr_init()` (p. 10), `globus_gass_copy_attr_set_io()` (p. 11), `globus_gass_copy_attr_set_ftp()` (p. 11), `globus_gass_copy_get_url_mode()` (p. 12), `globus_gass_transfer_requestattr_*`

5.1.2.15 `globus_result_t globus_gass_copy_get_url_mode (char * url, globus_gass_copy_url_mode_t * mode)`

Classify the URL schema into the transfer method that will be used to do the actual transfer.

This function enables the user to determine what protocol will be used to transfer data to/from a particular url. This information can then be used to specify the appropriate attributes when initiating a transfer.

Parameters:

url The URL for schema checking
mode the filled in schema type of the URL param

Returns:

This function returns `GLOBUS_SUCCESS` if successful, or a `globus_result_t` indicating the error that occurred.

See also:

`globus_gass_copy_attr_init()` (p. 10), `globus_gass_copy_attr_set_io()` (p. 11), `globus_gass_copy_attr_set_ftp()` (p. 11), `globus_gass_copy_set_gass()`

5.1.2.16 `globus_result_t globus_gass_copy_register_performance_cb (globus_gass_copy_handle_t * handle, globus_gass_copy_performance_cb_t callback, void * user_arg)`

Register a performance information callback.

Use this to register a performance information callback. You change or set to `GLOBUS_NULL` the callback any time a transfer is not occurring.

Parameters:

handle an initialized gass copy handle for which you would like to see performance info
callback the performance callback
user_arg a user pointer that will be passed to all callbacks for a given handle

Returns:

- GLOBUS_SUCCESS
- error on a NULL or busy handle

See also:

`globus_gass_copy_performance_cb_t` (p. 19)

5.1.2.17 globus_result_t globus_gass_copy_get_status (globus_gass_copy_handle_t * *handle*, globus_gass_copy_status_t * *status*)

Get the status code of the current transfer.

Get the status of the last transfer to be initiated using the given handle. Only one transfer can be active on a handle at a given time, therefore new transfers may only be initiated when the current status is one of the following: GLOBUS_GASS_COPY_STATUS_NONE, GLOBUS_GASS_COPY_STATUS_DONE_SUCCESS, GLOBUS_GASS_COPY_STATUS_DONE_FAILURE, GLOBUS_GASS_COPY_STATUS_DONE_CANCELLED

Parameters:

handle A globus_gass_copy_handle

status Will be one of the following: GLOBUS_GASS_COPY_STATUS_NONE (No transfers have been initiated using this handle.) GLOBUS_GASS_COPY_STATUS_PENDING (A transfer is currently being set up.) GLOBUS_GASS_COPY_STATUS_TRANSFER_IN_PROGRESS (There is currently a transfer in progress.) GLOBUS_GASS_COPY_STATUS_CANCEL (The last transfer initiated using this handle has been cancelled by the user before completing, and is in the process of being cleaned up.) GLOBUS_GASS_COPY_STATUS_FAILURE (The last transfer initiated using this handle failed, and is in the process of being cleaned up.) GLOBUS_GASS_COPY_STATUS_DONE_SUCCESS (The last transfer initiated using this handle has completed successfully.) GLOBUS_GASS_COPY_STATUS_DONE_FAILURE (The last transfer initiated using this handle failed and has finished cleaning up.) GLOBUS_GASS_COPY_STATUS_DONE_CANCELLED (The last transfer initiated using this handle was cancelled and has finished cleaning up.)

Returns:

This function returns GLOBUS_SUCCESS if successful, or a globus_result_t indicating the error that occurred.

5.1.2.18 const char* globus_gass_copy_get_status_string (globus_gass_copy_handle_t * *handle*)

Get the status string of the current transfer.

Get the status of the last transfer to be initiated using the given handle. Only one transfer can be active on a handle at a given time, therefore new transfers may only be initiated when the current status is one of the following: GLOBUS_GASS_COPY_STATUS_NONE, GLOBUS_GASS_COPY_STATUS_DONE_SUCCESS, GLOBUS_GASS_COPY_STATUS_DONE_FAILURE, GLOBUS_GASS_COPY_STATUS_DONE_CANCELLED

Parameters:

handle A globus_gass_copy_handle

Returns:

Returns a pointer to a character string describing the current status

5.1.2.19 `globus_result_t globus_gass_copy_url_to_url (globus_gass_copy_handle_t * handle, char * source_url, globus_gass_copy_attr_t * source_attr, char * dest_url, globus_gass_copy_attr_t * dest_attr)`

Transfer data from source URL to destination URL (blocking).

Parameters:

handle The handle to perform the copy operation

source_url transfer data from this URL

source_attr Attributes describing how the transfer from the source should be done

dest_url transfer data to this URL

dest_attr Attributes describing how the transfer to the destination should be done

Returns:

This function returns GLOBUS_SUCCESS if the transfer was completed successfully, or a result pointing to an object of one of the the following error types:

Return values:

GLOBUS_GASS_COPY_ERROR_TYPE_NULL_PARAMETER The handle was equal to GLOBUS_NULL, so the transfer could not processed.

GLOBUS_GASS_COPY_ERROR_TYPE_next_error next error description

See also:

`globus_gass_copy_url_to_handle()` (p. 14) `globus_gass_copy_handle_to_url()` (p. 15)

5.1.2.20 `globus_result_t globus_gass_copy_url_to_handle (globus_gass_copy_handle_t * handle, char * source_url, globus_gass_copy_attr_t * source_attr, globus_io_handle_t * dest_handle)`

Transfer data from source URL to an IO handle (blocking).

Parameters:

handle The handle to perform the copy operation

source_url transfer data from this URL

source_attr Attributes describing how the transfer from the source should be done

dest_handle transfer data to this IO handle

Returns:

This function returns GLOBUS_SUCCESS if the transfer was completed successfully, or a result pointing to an object of one of the the following error types:

Return values:

GLOBUS_GASS_COPY_ERROR_TYPE_NULL_PARAMETER The handle was equal to GLOBUS_NULL, so the transfer could not processed.

GLOBUS_GASS_COPY_ERROR_TYPE_next_error next error description

See also:

`globus_gass_copy_url_to_url()` (p. 14) `globus_gass_copy_handle_to_url()` (p. 15)

5.1.2.21 `globus_result_t globus_gass_copy_handle_to_url (globus_gass_copy_handle_t * handle, globus_io_handle_t * source_handle, char * dest_url, globus_gass_copy_attr_t * dest_attr)`

Transfer data from an IO handle to destination URL (blocking).

Parameters:

handle The handle to perform the copy operation

source_handle transfer data from this IO handle

dest_url transfer data to this URL

dest_attr Attributes describing how the transfer to the destination should be done

Returns:

This function returns GLOBUS_SUCCESS if the transfer was completed successfully, or a result pointing to an object of one of the the following error types:

Return values:

GLOBUS_GASS_COPY_ERROR_TYPE_NULL_PARAMETER The handle was equal to GLOBUS_NULL, so the transfer could not processed.

GLOBUS_GASS_COPY_ERROR_TYPE_next_error next error description

See also:

`globus_gass_copy_url_to_url()` (p. 14) `globus_gass_copy_url_to_handle()` (p. 14)

5.1.2.22 `globus_result_t globus_gass_copy_register_url_to_url (globus_gass_copy_handle_t * handle, char * source_url, globus_gass_copy_attr_t * source_attr, char * dest_url, globus_gass_copy_attr_t * dest_attr, globus_gass_copy_callback_t callback_func, void * callback_arg)`

Transfer data from source URL to destination URL (non-blocking).

This functions initiates a transfer from source URL to destination URL, then returns immediately.

When the transfer is completed or if the transfer is aborted, the *callback_func* will be invoked with the final status of the transfer.

Parameters:

handle The handle to perform the copy operation

source_url transfer data from this URL

source_attr Attributes describing how the transfer form the source should be done

dest_url transfer data to this URL

dest_attr Attributes describing how the transfer to the destination should be done

callback_func Callback to be invoked once the transfer is completed.

callback_arg Argument to be passed to the *callback_func*.

Returns:

This function returns GLOBUS_SUCCESS if the transfer was initiated successfully, or a result pointing to an object of one of the the following error types:

Return values:

GLOBUS_GASS_COPY_ERROR_TYPE_NULL_PARAMETER The handle was equal to GLOBUS_NULL, so the transfer could not processed.

GLOBUS_GASS_COPY_ERROR_TYPE_next_error next error description

See also:

globus_gass_copy_register_url_to_handle() (p. 16), **globus_gass_copy_register_handle_to_url()** (p. 16)

5.1.2.23 globus_result_t globus_gass_copy_register_url_to_handle (globus_gass_copy_handle_t * *handle*, char * *source_url*, globus_gass_copy_attr_t * *source_attr*, globus_io_handle_t * *dest_handle*, globus_gass_copy_callback_t *callback_func*, void * *callback_arg*)

Transfer data from source URL to an IO handle (non-blocking).

This functions initiates a transfer from source URL to an IO handle, then returns immediately.

When the transfer is completed or if the transfer is aborted, the *callback_func* will be invoked with the final status of the transfer.

Parameters:

handle The handle to perform the copy operation

source_url transfer data from this URL

source_attr Attributes describing how the transfer form the source should be done

dest_handle transfer data to this IO handle

callback_func Callback to be invoked once the transfer is completed.

callback_arg Argument to be passed to the *callback_func*.

Returns:

This function returns **GLOBUS_SUCCESS** if the transfer was initiated successfully, or a result pointing to an object of one of the the following error types:

Return values:

GLOBUS_GASS_COPY_ERROR_TYPE_NULL_PARAMETER The handle was equal to **GLOBUS_NULL**, so the transfer could not processed.

GLOBUS_GASS_COPY_ERROR_TYPE_next_error next error description

See also:

globus_gass_copy_register_url_to_url() (p. 15), **globus_gass_copy_register_handle_to_url()** (p. 16)

5.1.2.24 globus_result_t globus_gass_copy_register_handle_to_url (globus_gass_copy_handle_t * *handle*, globus_io_handle_t * *source_handle*, char * *dest_url*, globus_gass_copy_attr_t * *dest_attr*, globus_gass_copy_callback_t *callback_func*, void * *callback_arg*)

Transfer data from an IO handle to destination URL (non-blocking).

This functions initiates a transfer from an IO handle to destination URL, then returns immediately.

When the transfer is completed or if the transfer is aborted, the *callback_func* will be invoked with the final status of the transfer.

Parameters:

handle The handle to perform the copy operation

source_handle transfer data from this IO handle

dest_url transfer data to this URL

dest_attr Attributes describing how the transfer to the destination should be done

callback_func Callback to be invoked once the transfer is completed.

callback_arg Argument to be passed to the *callback_func*.

Returns:

This function returns GLOBUS_SUCCESS if the transfer was initiated successfully, or a result pointing to an object of one of the the following error types:

Return values:

GLOBUS_GASS_COPY_ERROR_TYPE_NULL_PARAMETER The handle was equal to GLOBUS_NULL, so the transfer could not processed.

GLOBUS_GASS_COPY_ERROR_TYPE_next_error next error description

See also:

globus_gass_copy_register_url_to_url() (p. 15), **globus_gass_copy_register_url_to_handle()** (p. 16)

5.1.2.25 globus_result_t globus_gass_copy_cache_url_state (globus_gass_copy_handle_t * *handle*, char * *url*)

Cache connections to an FTP or GSIFTP server.

Explicitly cache connections to URL server. When an URL is cached, the connection to the URL server will not be closed after a file transfer completes.

Parameters:

handle Handle which will contain a cached connection to the URL server.

url The URL of the FTP or GSIFTP server to cache.

Returns:

This function returns GLOBUS_SUCCESS if successful, or a globus_result_t indicating the error that occurred.

5.1.2.26 globus_result_t globus_gass_copy_flush_url_state (globus_gass_copy_handle_t * *handle*, char * *url*)

Remove a cached connection to an FTP or GSIFTP server.

Explicitly remove a cached connection to an FTP or GSIFTP server. If an idle connection to an FTP server exists, it will be closed.

Parameters:

handle Handle which contains a cached connection to the URL server.

url The URL of the FTP or GSIFTP server to remove.

Returns:

This function returns GLOBUS_SUCCESS if successful, or a globus_result_t indicating the error that occurred.

5.1.2.27 `globus_result_t globus_gass_copy_set_user_pointer (globus_gass_copy_handle_t * handle, void * user_pointer)`

Set a pointer in the handle to point at user-allocated memory.

5.1.2.28 `globus_result_t globus_gass_copy_get_user_pointer (globus_gass_copy_handle_t * handle, void ** user_data)`

Get the pointer in the handle that points to user-allocated memory.

5.1.2.29 `globus_result_t globus_gass_copy_cancel (globus_gass_copy_handle_t * handle, globus_gass_copy_callback_t cancel_callback, void * cancel_callback_arg)`

Cancel the current transfer associated with this handle,.

store the `cancel_callback` and `cancel_callback_arg` in the handle. Needed because the ftp callback will be the one given from the original `globus_ftp_client_third_party_transfer()` call.

5.1.2.30 `globus_result_t globus_l_gass_copy_target_cancel (globus_i_gass_copy_cancel_t * cancel_info)`

Cancel the source or destination transfer in progress.

5.2 globus_gass_copy.h File Reference

Header file for the gass copy library.

Data Structures

- struct `globus_gass_copy_glob_stat_t`
Glob expanded entry information.

Defines

- `#define GLOBUS_GASS_COPY_MODULE (&globus_i_gass_copy_module)`

Typedefs

- `typedef void(*) globus_gass_copy_performance_cb_t (void *user_arg, globus_gass_copy_handle_t *handle, globus_off_t total_bytes, float instantaneous_throughput, float avg_throughput)`
- `typedef void(*) globus_gass_copy_glob_entry_cb_t (const char *url, const globus_gass_copy_glob_stat_t *info_stat, void *user_arg)`

Enumerations

- enum `globus_gass_copy_glob_entry_t`

Functions

- `globus_result_t globus_gass_copy_glob_expand_url (globus_gass_copy_handle_t *handle, const char *url, globus_gass_copy_attr_t *attr, globus_gass_copy_glob_entry_cb_t entry_cb, void *user_arg)`
- `globus_result_t globus_gass_copy_mkdir (globus_gass_copy_handle_t *handle, char *url, globus_gass_copy_attr_t *attr)`

5.2.1 Detailed Description

Header file for the gass copy library.

5.2.2 Define Documentation

5.2.2.1 #define GLOBUS_GASS_COPY_MODULE (&globus_i_gass_copy_module)

Module descriptor.

Globus GASS Copy uses standard Globus module activation and deactivation. Before any Globus GASS Copy functions are called, the following function must be called:

```
globus_module_activate(GLOBUS_GASS_COPY_MODULE)
```

This function returns GLOBUS_SUCCESS if Globus GASS Copy was successfully initialized, and you are therefore allowed to subsequently call Globus GASS Copy functions. Otherwise, an error code is returned, and Globus GASS Copy functions should not be subsequently called. This function may be called multiple times.

To deactivate Globus GASS Copy, the following function must be called:

```
globus_module_deactivate(GLOBUS_GASS_COPY_MODULE)
```

This function should be called once for each time Globus GASS Copy was activated.

5.2.3 Typedef Documentation

5.2.3.1 typedef void(*) globus_gass_copy_performance_cb_t(void *user_arg, globus_gass_copy_handle_t *handle, globus_off_t total_bytes, float instantaneous_throughput, float avg_throughput)

Gass copy transfer performance callback.

This callback is registered with 'globus_gass_copy_register_performance_cb'. It will be called during a transfer to supply performance information on current transfer. Its frequency will be at most one per second, but it is possible to receive no callbacks. This is possible in very short transfers and in ftp transfers in which the server does not provide performance information.

Parameters:

handle the gass copy handle this transfer is occurring on

user_arg a user pointer registered with 'globus_gass_copy_register_performance_cb'

total_bytes the total number of bytes transfer so far

instantaneous_throughput instantaneous rate of transfer (since last callback or start) (bytes / sec)

avg_throughput the avg throughput calculated since the start of the transfer (bytes / sec)

Returns:

- n/a

5.2.3.2 `typedef void(*) globus_gass_copy_glob_entry_cb_t(const char *url, const globus_gass_copy_glob_stat_t *info_stat, void *user_arg)`

Gass copy glob entry callback.

This callback is passed as a parameter to `globus_gass_copy_glob_expand_url()` (p. 20). It is called once for each entry that the original expands to.

Parameters:

url The full url to the expanded entry. A directory entry will end in a forward slash '/'.

stat A pointer to a `globus_gass_copy_glob_stat_t` (p. 2) containing information about the entry.

user_arg The *user_arg* passed to `globus_gass_copy_glob_expand()`

See also:

`globus_gass_copy_glob_stat_t` (p. 2), `globus_gass_copy_glob_expand_url` (p. 20)

5.2.4 Enumeration Type Documentation

5.2.4.1 `enum globus_gass_copy_glob_entry_t`

globbed entry types

5.2.5 Function Documentation

5.2.5.1 `globus_result_t globus_gass_copy_glob_expand_url (globus_gass_copy_handle_t * handle, const char * url, globus_gass_copy_attr_t * attr, globus_gass_copy_glob_entry_cb_t entry_cb, void * user_arg)`

Expand globbed url.

This function expands wildcards in a globbed url, and calls `entry_cb()` on each one.

Parameters:

handle A gass copy handle to use for the operation.

url The URL to expand. The URL may be an ftp, gsiftp or file URL. Wildcard characters supported are '?' '*' '[' ']' in the filename portion of the url.

attr Gass copy attributes for this operation.

entry_cb Function to call with information about each entry

user_arg An argument to pass to `entry_cb()`

Returns:

This function returns an error when any of these conditions are true:

- *handle* is `GLOBUS_NULL`
- *url* is `GLOBUS_NULL`
- *url* cannot be parsed
- *url* is not a ftp, gsiftp or file url

5.2.5.2 `globus_result_t globus_gass_copy_mkdir (globus_gass_copy_handle_t * handle, char * url, globus_gass_copy_attr_t * attr)`

Make directory.

This function creates a directory given a ftp or file url.

Parameters:

handle A gass copy handle to use for the mkdir operation.

url The URL for the directory to create. The URL may be an ftp, gsiftp or file URL.

attr Gass copy attributes for this operation.

Returns:

This function returns an error when any of these conditions are true:

- handle is GLOBUS_NULL
- url is GLOBUS_NULL
- url cannot be parsed
- url is not a ftp, gsiftp or file url
- the directory could not be created

Index

attr
 globus_i_gass_copy_state_target_s, 4

cancel
 globus_gass_copy_state_s, 3

data
 globus_i_gass_copy_state_target_s, 5

dest
 globus_gass_copy_state_s, 3

free_handle
 globus_i_gass_copy_state_target_s, 5

ftp
 globus_i_gass_copy_state_target_s, 5

gass
 globus_i_gass_copy_state_target_s, 5

globus_gass_copy.c, 6
 globus_gass_copy_attr_init, 10
 globus_gass_copy_attr_set_ftp, 10
 globus_gass_copy_attr_set_gass, 11
 globus_gass_copy_attr_set_io, 11
 globus_gass_copy_cache_url_state, 16
 globus_gass_copy_cancel, 17
 globus_gass_copy_flush_url_state, 17
 globus_gass_copy_get_buffer_length, 8
 globus_gass_copy_get_no_third_party_transfers, 9
 globus_gass_copy_get_partial_offsets, 10
 globus_gass_copy_get_status, 12
 globus_gass_copy_get_status_string, 13
 globus_gass_copy_get_url_mode, 11
 globus_gass_copy_get_user_pointer, 17
 globus_gass_copy_handle_destroy, 7
 globus_gass_copy_handle_init, 7
 globus_gass_copy_handle_to_url, 14
 globus_gass_copy_register_handle_to_url, 16
 globus_gass_copy_register_performance_cb, 12
 globus_gass_copy_register_url_to_handle, 15
 globus_gass_copy_register_url_to_url, 15
 globus_gass_copy_set_allocate, 9
 globus_gass_copy_set_buffer_length, 8
 globus_gass_copy_set_no_third_party_transfers, 8
 globus_gass_copy_set_partial_offsets, 9
 globus_gass_copy_set_stat_on_expand, 9
 globus_gass_copy_set_user_pointer, 17
 globus_gass_copy_url_to_handle, 14
 globus_gass_copy_url_to_url, 13
 globus_l_gass_copy_target_cancel, 17

globus_gass_copy.h, 18
 globus_gass_copy_glob_entry_cb_t, 19
 globus_gass_copy_glob_entry_t, 19
 globus_gass_copy_glob_expand_url, 20
 globus_gass_copy_mkdir, 20
 GLOBUS_GASS_COPY_MODULE, 18
 globus_gass_copy_performance_cb_t, 19

globus_gass_copy_attr_init
 globus_gass_copy.c, 10

globus_gass_copy_attr_set_ftp
 globus_gass_copy.c, 10

globus_gass_copy_attr_set_gass
 globus_gass_copy.c, 11

globus_gass_copy_attr_set_io
 globus_gass_copy.c, 11

globus_gass_copy_cache_url_state
 globus_gass_copy.c, 16

globus_gass_copy_cancel
 globus_gass_copy.c, 17

globus_gass_copy_flush_url_state
 globus_gass_copy.c, 17

globus_gass_copy_get_buffer_length
 globus_gass_copy.c, 8

globus_gass_copy_get_no_third_party_transfers
 globus_gass_copy.c, 9

globus_gass_copy_get_partial_offsets
 globus_gass_copy.c, 10

globus_gass_copy_get_status
 globus_gass_copy.c, 12

globus_gass_copy_get_status_string
 globus_gass_copy.c, 13

globus_gass_copy_get_url_mode
 globus_gass_copy.c, 11

globus_gass_copy_get_user_pointer
 globus_gass_copy.c, 17

globus_gass_copy_glob_entry_cb_t
 globus_gass_copy.h, 19

globus_gass_copy_glob_entry_t
 globus_gass_copy.h, 19

globus_gass_copy_glob_expand_url
 globus_gass_copy.h, 20

globus_gass_copy_glob_stat_t, 1
 mdtm, 2
 mode, 2
 size, 2
 symlink_target, 2
 type, 2
 unique_id, 2

globus_gass_copy_handle_destroy
 globus_gass_copy.c, 7

globus_gass_copy_handle_init
 globus_gass_copy.c, 7

globus_gass_copy_handle_to_url
 globus_gass_copy.c, 14

globus_gass_copy_mkdir

- globus_gass_copy.h, 20
- GLOBUS_GASS_COPY_MODULE
 - globus_gass_copy.h, 18
- globus_gass_copy_performance_cb_t
 - globus_gass_copy.h, 19
- globus_gass_copy_register_handle_to_url
 - globus_gass_copy.c, 16
- globus_gass_copy_register_performance_cb
 - globus_gass_copy.c, 12
- globus_gass_copy_register_url_to_handle
 - globus_gass_copy.c, 15
- globus_gass_copy_register_url_to_url
 - globus_gass_copy.c, 15
- globus_gass_copy_set_allocate
 - globus_gass_copy.c, 9
- globus_gass_copy_set_buffer_length
 - globus_gass_copy.c, 8
- globus_gass_copy_set_no_third_party_transfers
 - globus_gass_copy.c, 8
- globus_gass_copy_set_partial_offsets
 - globus_gass_copy.c, 9
- globus_gass_copy_set_stat_on_expand
 - globus_gass_copy.c, 9
- globus_gass_copy_set_user_pointer
 - globus_gass_copy.c, 17
- globus_gass_copy_state_s, 2
 - cancel, 3
 - dest, 3
 - monitor, 3
 - mutex, 3
 - source, 3
- globus_gass_copy_url_to_handle
 - globus_gass_copy.c, 14
- globus_gass_copy_url_to_url
 - globus_gass_copy.c, 13
- globus_i_gass_copy_buffer_t, 3
- globus_i_gass_copy_cancel_s, 3
- globus_i_gass_copy_monitor_t, 4
- globus_i_gass_copy_state_target_s, 4
 - attr, 4
 - data, 5
 - free_handle, 5
 - ftp, 5
 - gass, 5
 - io, 5
 - mode, 5
 - mutex, 4
 - n_complete, 5
 - n_pending, 5
 - n_simultaneous, 5
 - queue, 5
 - request, 5
 - seekable, 5
 - status, 5
 - url, 4
- globus_l_gass_copy_target_cancel

- globus_gass_copy.c, 17
- io
 - globus_i_gass_copy_state_target_s, 5
- mdtm
 - globus_gass_copy_glob_stat_t, 2
- mode
 - globus_gass_copy_glob_stat_t, 2
 - globus_i_gass_copy_state_target_s, 5
- monitor
 - globus_gass_copy_state_s, 3
- mutex
 - globus_gass_copy_state_s, 3
 - globus_i_gass_copy_state_target_s, 4
- n_complete
 - globus_i_gass_copy_state_target_s, 5
- n_pending
 - globus_i_gass_copy_state_target_s, 5
- n_simultaneous
 - globus_i_gass_copy_state_target_s, 5
- queue
 - globus_i_gass_copy_state_target_s, 5
- request
 - globus_i_gass_copy_state_target_s, 5
- seekable
 - globus_i_gass_copy_state_target_s, 5
- size
 - globus_gass_copy_glob_stat_t, 2
- source
 - globus_gass_copy_state_s, 3
- status
 - globus_i_gass_copy_state_target_s, 5
- symlink_target
 - globus_gass_copy_glob_stat_t, 2
- type
 - globus_gass_copy_glob_stat_t, 2
- unique_id
 - globus_gass_copy_glob_stat_t, 2
- url
 - globus_i_gass_copy_state_target_s, 4